

# NSGDatacom Inc.

## Model 1280T - PSK

### Tactical/Airborne HF Data Modem

- **Airborne Qualified**
- **Multi-Mode PSK or FSK**
- **Synchronous or Asynchronous Operation**
- **Full or Half Duplex Operation**
- **Built-in Test Capability**
- **Excision Filtering**
- **KG-84/KG-84C Compatible**

The Model 1280T - PSK is a high performance, multi-mode HF data modem capable of transmitting and receiving up to 4800 bits per second in a standard 3KHz sideband HF radio channel. Packaged in a ruggedized tactical/airborne enclosure, the modem has been qualified as meeting the rigid environmental requirements for shock, vibration, temperature, EMI, acceleration, altitude, immersion and other extreme environmental conditions. The Model 1280T - PSK utilizes ATR style mounting for seamless installation in any airborne or tactical platform.

Designed to meet the performance requirements of MIL-STD-188-110A, STANAG 4285, STANAG 4529, and STANAG 4481, the Model 1280T - PSK provides additional flexibility due to its compatibility with other widely used FSK modems. It features full duplex / half duplex operation, and a synchronous or asynchronous DTE interface.

A powerful adaptive equalizer eliminates the detrimental effects of multipath associated with HF transmissions, and convolutional coding with soft decision Viterbi decoding provides error detection and correction. Protection against co-site interference is provided by excision filtering, which automatically removes unwanted interfering signals.

Additional operational modes can be supported with the modems powerful Digital Signal Processing (DSP) design, and expanded memory. Standard Flash memory provides the ability to perform software upgrades in the field.



# 1280T - PSK Specifications

## Model 1280T - PSK

### Environmental

**Shock:** Operational: RTCA/DO-160-C, Section 7, Paragraph 7.2  
Bench Handling: MIL-STD-810E, Method 516.4, Procedure VI

**Vibration:** BS 3G.100: Part 2: Section 3: Subsection 3.1  
MIL-STD-810D, Method 514.3, Category 8

**Temperature:** BS 3G.100: Part 2: Subsection 3.2 aircraft class 2  
subsonic, Grade "A".  
Operating - 30 C to +55 C,  
Non-Operating -40 C to +90 C;  
In-Flight -15 C to +36 C.

**Rapid Decompression:** RTCA/DO-160-C, Section 4, Paragraph 4.6.2

**Overpressure:** RTCA/DO-160-C, Section 4, Paragraph 4.6.3

**Acceleration:** BS 3G.100: Part 2: Section 3, Subsection 3.6 Normal: Grade "D", Crash: Grade "G"

**Magnetic Influence:** RTCA/DO-160-C, Section 15, Equipment Class "Z"

**Immersion:** MIL-STD-810D, Method 512.2, Procedure I, Basic Leak

**Humidity:** MIL-STD-507.2, Procedure III, Humidity Cycles

**Fungus:** MIL-STD-810D, Method 508.3, 28 days

**Sand and Dust:** MIL-STD-810D, Method 510.2, Procedure I, Blowing Dust

**Salt Fog:** MIL-STD-810D, Method 509.2, 5% salt solution for 48 hours

### Interfaces

**Data:** MIL-STD-188-114, MIL-STD-188C,  
EIA-RS-422 and EIA-RS-432 compatible  
(synchronous or asynchronous)

**Audio:** 600 ohms balanced and isolated

### Serial Tone Mode

**Data Rates:**  
75, 150, 300, 600, 1200, 2400 and 4800 bps

### Interoperability:

- MIL-STD-188-110A
- STANAG 4285
- STANAG 4529

### Modulation:

8-ARY PSK at 2400 symbols per second

### Error Detection and Correction:

Convolutional coding with soft decision  
Viterbi decoding

### Interleaving:

Selectable at 0.6 or 4.8 seconds or no interleaving.

### FSK Mode

**Data Rates:**  
50, 75, 100, 150, 300, 600 and 1200 bps

### Modulation:

Phase continuous binary FSK

### Mark/Space Frequency:

300 to 3000 Hz (selectable in 1 Hz increments)

### Shift:

85 to 1200 Hz

### Physical

#### Size: ¾ ATR

7.6" (19.3 cm) H  
X 7.5" (19.05cm) W  
X 15.8" (40.13cm) D

**Weight:** 15 lbs (6.8kg)

**Dual Rack:** Adaptor for 19" rack mount of two  
1280Ts, 1280TAs or KG-84As

### Electrical

**Power:** Source: 11 to 32 VDC

Dissipation: 35 watts maximum

### AC/DC Supply:

AC from 90 to 265 volts  
DC from 11 to 32 volts



- **Remote Controllable**
- **AC/DC Power Options**
- **Non-Volatile 10 Channel Memory**
- **RX Clock Recovery**
- **Internal or External Clock**

**NSGDatacom Inc.**

7435 New Technology Way, Frederick, Maryland 21703

Phone: 301.662.5926 Fax: 301.694.6279

www.nsgdata.com

Specifications subject to change without notice.